

Μηχανές καφέ με ατμό - Coffee Machines with Steam

	°dKH	Ρύθμιση Bypass	Filter capacity in litres - Απόδοση φίλτρου σε λίτρα						
			X	S	V	M	L	XL	2XL
Προσωρινή Σκληρότητα Temporary Hardness	≤7	3	855	1425	3570	5425	7425	9710	17140
	8	3	750	1250	3125	4750	6500	8500	15000
	9	3	665	1110	2775	4220	5775	7555	13330
	10	3	600	1000	2500	3800	5200	6800	12000
	11	2	485	815	2035	3095	4235	5540	9780
	12	2	445	745	1865	2835	3885	5080	8965
	13	2	410	690	1720	2620	3585	4690	8275
	14	2	380	640	1600	2430	3330	4355	7685
	15	2	355	595	1490	2270	3105	4060	7170
	16-18	1	280	470	1185	1800	2465	3220	5690
	19-21	1	240	395	995	1515	2075	2715	4790
	22-24	1	205	345	860	1310	1790	2345	4135
	25	1	180	300	755	1150	1575	2060	3640

Μηχανές καφέ χωρίς ατμό - Coffee Machines without Steam

	°dKH	Ρύθμιση Bypass	Filter capacity in litres - Απόδοση φίλτρου σε λίτρα						
			X	S	V	M	L	XL	2XL
Προσωρινή Σκληρότητα Temporary Hardness	≤7	3	≥1025	≥1710	≥4285	≥6510	≥8910	≥11655	≥20570
	8	3	900	1500	3750	5700	7800	10200	18000
	9	3	800	1330	3330	5065	6930	9065	16000
	10	3	720	1200	3000	4560	6240	8160	14400
	11	2	655	1090	2725	4145	5670	7415	13090
	12	2	600	1000	2500	3800	5200	6800	12000
	13	2	550	920	2305	3505	4800	6275	11075
	14	2	510	855	2140	3255	4455	5825	10285
	15	2	480	800	2000	3040	4160	5440	9600
	16-18	1	420	705	1765	2680	3670	4800	8470
	19-21	1	360	600	1500	2280	3120	4080	7200
	22-24	1	310	520	1300	1980	2710	3545	6260
	25	1	≤255	≤430	≤1075	≤1635	≤2235	≤2925	≤5160